



Model No.	Parts no. ①③④⑥	
	Material	Surface Finish
GFK □□ - S □ B	S50C	Black Dyed
GFK □□ - S □ N		Ni-Plating

GFK-B



Specification

Standard Type			Dimensions												
Light pre-loaded	Medium pre-loaded	Hard pre-loaded	∅d	∅R	□G	T	H	F	∅Dg6	E	Installation (A)		Installation (B)		PCD
											T1	E1	T2	E2	
GFK06-SL □	GFK06-SM □	GFK06-SH □	6	36	28	20	7	13	22 ^{±0.015}	22	5.5	3.5	6.5	4.5	28
GFK08-SL □	GFK08-SM □	GFK08-SH □	8	43	35	23	9	14	28 ^{±0.020}	26	7	4	8	5	35
GFK10-SL □	GFK10-SM □	GFK10-SH □	10	52	42	27	10	17	34 ^{±0.025}	29.5	7.3	5	8.5	6	42
GFK12-SL □	GFK12-SM □	GFK12-SH □	12	54	44	27	10	17	36 ^{±0.030}	29.5	7.3	5	8.5	6	44
GFK15-SL □	GFK15-SM □	GFK15-SH □	15	63	52	32	15	17	40 ^{±0.035}	36	9.8	6	12	8	50
GFK17-SL □	GFK17-SM □	GFK17-SH □	17	77	61	45	22	23	50 ^{±0.040}	47	11	9	14	12	62
GFK20-SL □	GFK20-SM □	GFK20-SH □	20	85	68	52	22	30	57 ^{±0.045}	50	7.8	10	12	14	70
GFK25-SL □	GFK25-SM □	GFK25-SH □	25	98	79	57	27	30	63 ^{±0.050}	60	12.8	10	20	17	80
GFK30-SL □	GFK30-SM □	GFK30-SH □	30	117	93	62	30	32	75 ^{±0.055}	61	10.8	12	17	18	95

Ordering Example	GFK	10	SL	N	J
	Model No.	Shaft Dia.	Grade/Pre-loaded	Surface finish	Bearing category



GFK-N




Components

No.	Parts	Material	Q'ty
①	Main housing	S50C	1
②	Bearing	SUJ2	1 pair
③	Cover	S50C	1
④	Space ring	S50C	2
⑤	Seal (<∅8 one seal only)	NBR	2
⑥	Lucknut	S50C	1

- ①②③ are in one unit. No disassemble for accuracy concern.
- Bearing filled with proper lithium soap lubricant and sealed.

Recommended processing dimensions of shaft



Unit : mm

											Recommended processing dimensions of shaft					
∅d1	∅d2	Z	M1	□S	∅D	∅d	Processing sizes of shaft			Nominal thread		Space ring length				
							∅A	B	C	M	L	T4				
3.4	6	3.3	M3	12	8	6 ^{±0.015}	4	28	8	M6*P0.75	8	5				
3.4	6	3.3	M3	14	10 / 12	8 ^{±0.015}	6	32	9	M8*P1.0	10	5.5				
4.5	8	4	M3	16	12 / 14 / 15	10 ^{±0.020}	8	36	15	M10*P1.0	11	5.5				
4.5	8	4	M3	19	14 / 15 / 16	12 ^{±0.020}	10	36	15	M12*P1.0	11	5.5				
5.5	9.5	6	M3	22	18 / 20	15 ^{±0.025}	12	47	20	M15*P1.0	13	10				
6.6	11	10	M4	24	20 / 25	17 ^{±0.030}	15	53	23	M17*P1.0	17	7				
6.5	11	10	M4	30	25 / 28 / 30	20 ^{±0.035}	17	62	25	M20*P1.0	17	11				
9	15	13	M5	35	30 / 32 / 36	25 ^{±0.040}	20	76	30	M25*P1.5	20	15				
11	17.5	15	M6	40	36 / 40	30 ^{±0.045}	25	72	38	M30*P1.5	25	9				

• Supported Side spec refer to P.36~P.37